

FT26MH

NuArc's FT26MH FlipTop Exposure System features a 1000-watt multi-spectrum metal halide lamp that delivers fast, precise exposures. Its lamp, with instant-start, shutterless operation, makes it ideal for virtually every type of photosensitive material, including all color proofing materials and offset plates. The digital LED integrator on the FT26MH ensures exact exposure repeatability. The energy-efficient power supply provides more power and light at lower wattages than many competing products.

Only 34 inches (86 cm) square, the compact FT26MH fits almost anywhere, yet provides a $23'' \times 27''$ (58 x 69 cm) usable area. FT26MH is available in 110v and 208/230v models.

Built with NuArc's attention to quality, durability, and design excellence, and backed by NuArc's award-winning service, the FT26MH is designed for dependable performance, low maintenance, and long life.

WWW puare co kr

FlipTop Exposure System

Standard Features

Controller/Integrator

• LED readout

Design & Construction

- · Attractive, compact design
- Enclosed light cabinet prevents accidental exposure of sensitized products
- Gas lift-arm assisted vacuum frame opening
- · Heavy-duty all-steel cabinet
- Molded one-piece blanket
- Rigid tubular aluminum glass frame

Electrical Requirements*

• 110v, 1 phase, 13 amps, 60 Hz

Light Source

- 1000-watt lamp
- Instant-start lamp and rapid recovery power supply provide shutterless operation
- Instant-start lamp eliminates warmup and idling times, saving energy
- · Multi-spectrum metal-halide lamp

Size (HxWxD)

- 37" x 34" x 34" (94 x 86 x 86 cm)
- Requires 3" (8 cm) of clearance at rear for ventilation

Vacuum System

• Heavy-duty maintenance-free vacuum pump for rapid drawdown

Support

• 24-hour hotline

Training

 Access to the M&R/NuArc Training Centers

Warranty

One-year limited warranty excluding glass and lamps



Options & Accessories

Electrical Requirements*

- 208/230v, 1 phase, 9.4/7.7 amps, 60 Hz
- 208/230v, 1 phase, 7.4/6.7 amps, 50 Hz

Filters

• Kokomo Filter (GW126)

Replacement Lamp

• NP 80

SPECIFICATIONS

Model	Wattage	Usable Area	Size (HxWxD)***	Electrical Requirements*	Shipping Weight
FT26MH	1000	23" x 27" (58 x 69 cm)	37" x 34" x 34" (94 x 86 x 86 cm)	110v, 1 phase, 13 amps, 60 Hz 208/230v, 1 phase, 9.4/7.7 amps, 60 Hz** 208/230v, 1 phase, 7.4/6.7 amps, 50 Hz**	370 lbs (816 kg)

- * If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly
- ** Optional
- *** Requires 3" (8 cm) of clearance at rear for ventilation

NUArc Company, Inc. is a wholly owned subsidiary of M&R Printing Equipment, Inc. Promotional information in this advertising brochure is believed accurate at the time of publication. However, NuArc and the manufacturer(s) of such products expressly disclaim any liability for damages, whether consequential or incidental, resulting from the purchase, installation, or use of any products or services based upon information depicted herein. The buyer's rights and reliedles, if any, are limited solely to those provided in writing by NuArc or the manufacturer at the time of sale. Nothing contained herein shall convey any additional rights to the buyer or impose any additional obligations on NuArc or any manufacturer. IN082101